


Produkta datu lapa

Specifikācijas



W300 MODULAR DEVICE RAIL PRISMA G



03010

Paziņojuma datums par preces pārtraukšanu 2024. gada 14. febr.

Pārtraukts

Galvenā

Diapazons	Prisma
Produkta Sērija	Prisma G
Produkta Vai Sastāvdaļas Veids	Rail
Aksesuāru / Rezerves Daļu Kategorija	Uzstādīšanas piederums
Saderība Ar	Prisma (Prisma G) duct
Sliedes Tips	Modular
Installed Device	Acti 9 fixed C120 without toggle TeSys fixed GV2LE TeSys fixed GV2ME TeSys fixed GV2RTn Acti 9 fixed iC120 without toggle ComPact fixed INS100 direct front rotary handle - vertikāli ComPact fixed INS160 direct front rotary handle - vertikāli ComPact fixed INS40 direct front rotary handle - vertikāli ComPact fixed INS63 direct front rotary handle - vertikāli Acti 9 fixed modular device Multi9 fixed modular device Multi9 fixed NG125 without toggle Multi9 fixed NG125 NA toggle Acti 9 fixed C120 with toggle Acti 9 fixed iC120 with toggle Multi9 fixed NG125 with toggle ComPact fixed INS125 direct front rotary handle - vertikāli Acti 9 fixed modular device <= 40 A Multi9 fixed modular device <= 40 A

Poles Description	1 x 3P fixed C120 1 x 4P fixed C120 1 x 3P fixed iC120 1 x 4P fixed iC120 1 x 3P fixed INS100 vertikāli 1 x 4P fixed INS100 vertikāli 1 x 3P fixed INS160 vertikāli 1 x 4P fixed INS160 vertikāli 1 x 3P fixed INS40 vertikāli 1 x 4P fixed INS40 vertikāli 1 x 3P fixed INS63 vertikāli 1 x 4P fixed INS63 vertikāli 1 x 3P fixed NG125 1 x 4P fixed NG125 1 x 3P fixed NG125 NA 1 x 4P fixed NG125 NA 1 x 3P fixed INS125 vertikāli 1 x 4P fixed INS125 vertikāli 4 x 3P fixed GV2LE 4 x 3P fixed GV2ME 4 x 3P fixed GV2RTn
-------------------	---

Papildinošs

Ir sasniegts maksimālais salīdzināmo produktu skaits. Lūdzu, atveriet sadaļu Salīdzināt produktus #SAITE# un izdzēsiet kādu produktu, lai turpinātu.

Installation Description	Floor-standing duct 300 mm Wall-mounted duct 300 mm
Number Of Vertical Modules [50 Mm]	4 C120 without, direct 300 mm floor-standing duct 4 C120 without, direct 300 mm wall-mounted duct 3 GV2LE, direct 300 mm floor-standing duct 3 GV2LE, direct 300 mm wall-mounted duct 3 GV2ME, direct 300 mm floor-standing duct 3 GV2ME, direct 300 mm wall-mounted duct 3 GV2RTn, direct 300 mm floor-standing duct 3 GV2RTn, direct 300 mm wall-mounted duct 4 iC120 without, direct 300 mm floor-standing duct 4 iC120 without, direct 300 mm wall-mounted duct 4 INS100, direct 300 mm floor-standing duct 4 INS100, direct 300 mm wall-mounted duct 5 INS100, direct 300 mm floor-standing duct 5 INS100, direct 300 mm wall-mounted duct 4 INS125, direct 300 mm floor-standing duct 4 INS125, direct 300 mm wall-mounted duct 5 INS125, direct 300 mm floor-standing duct 5 INS125, direct 300 mm wall-mounted duct 4 INS160, direct 300 mm floor-standing duct 4 INS160, direct 300 mm wall-mounted duct 5 INS160, direct 300 mm floor-standing duct 5 INS160, direct 300 mm wall-mounted duct 4 INS40, direct 300 mm floor-standing duct 4 INS40, direct 300 mm wall-mounted duct 4 INS63, direct 300 mm floor-standing duct 4 INS63, direct 300 mm wall-mounted duct 3 modular device <= 40 A, direct 300 mm floor-standing duct 3 modular device <= 40 A, direct 300 mm wall-mounted duct 4 modular device, direct 300 mm floor-standing duct 4 modular device, direct 300 mm wall-mounted duct 4 NG125 without, direct 300 mm floor-standing duct 4 NG125 without, direct 300 mm wall-mounted duct 4 NG125 NA, direct 300 mm floor-standing duct 4 NG125 NA, direct 300 mm wall-mounted duct 4 C120 with, direct 300 mm floor-standing duct 4 C120 with, direct 300 mm wall-mounted duct 4 iC120 with, direct 300 mm floor-standing duct 4 iC120 with, direct 300 mm wall-mounted duct 4 NG125 with, direct 300 mm floor-standing duct 4 NG125 with, direct 300 mm wall-mounted duct
9 Mm Atstarpe	20
Daudzums Komplektā	Komplektā 1
Augstums	52 mm
Platums	218 mm
Dziļums	100 mm
Neto Svars	0,14 kg
Krāsa	Natural
Materiāls	Metāls

Vide

Standarti	IEC 61439-1 IEC 61439-2
Produkta Sertifikācija	ASEFA

Iepakojšanas vienības

Pirmā Iepakojuma Vienības Tips	PCE
Vienību Skaits 1. Iepakojumā	1

Ilgtspējības nodaļa

Green Premium™ marķējums ir Schneider Electric apņemšanās piegādāt produktus ar savā klasē labākajiem vides rādītājiem. Green Premium apliecina atbilstību jaunākajiem noteikumiem, pārredzamību par ietekmi uz vidi, kā arī aprites un zema CO₂ produktiem.

Produktu ilgtspējības novērtēšanas rokasgrāmata ir baltā grāmata, kurā izskaidroti globālie ekomarķējuma standarti un tas, kā interpretēt vides deklarācijas.

[Rokasgrāmata produkta ilgtspējas novērtēšanai >](#)



Pārredzamība RoHS/REACH

Labklājības veikspēja

- ✓ Nesatur Reach Svhc
- ✓ Nesatur Toksiskus Smagos Metālus
- ✓ Nesatur Dzīvsudrabu
- ✓ Informācija Par Rohs Izņēmumiem [Jā](#)
- ✓ Produkta Plastmasas Detaļas Nesatur Halogēnus

Sertifikācijas un standarti

Es Rohs Direktīva	Proaktīva atbilstība (uz izstrādājumu neattiecas ES RoHS juridiskās saistības) ES RoHS deklarācija
Ķīnas Rohs Regula	Ķīnas RoHS deklarācija Ķīnas aktīvā RoHS deklarācija (neietilpst Ķīnas RoHS juridiskajā jomā)
Vides Informācijas Publiskošana	Produkta ietekme uz vidi